

GSM Transmitter 3

Portable GSM Data Transmitter for Sebalog N-3 and Sebalog P-3



Special features:

- Offers remote data transmission
- Fits even into small valve boxes
- Uses field replaceable batteries
- Is fully submersible
- Operates Wireless
- Carries data from up to three devices

Description

Patrolling noise and pressure loggers is time consuming and costly. The GSM Transmitter 3 (GT-3) can save you this trouble. It is designed to transmit data collected by noise and pressure loggers from the site to your office. Using GSM/GPRS, on site patrolling is no longer necessary. Save time, money and monitor your network from the office with the GT-3.

Small and fully submersible, the GSM Transmitter 3 is specifically designed to fit into valve boxes and hydrant chambers.

Up to three devices can be connected to the GSM Transmitter 3 - a benchmark in cost efficiency for GSM data transmission out of an underground chamber.

[Download datasheet](#)

Pictures



User manual

 [User manual GT-3 \(7.0 MB\)](#)


Software


Firmware GT-3


 [Version 1.011 \(Frequency 868 MHz\) \(113.8 KB\)](#)

 [Version 1.011 \(Frequency 916 MHz\) \(113.8 KB\)](#)

Firmware LOG CDR-3-1 (only for touch screen display)

 [Version 4.008 \(frequency 868 MHz\) \(1.3 MB\)](#)

 [Version 4.008 \(frequency 913 MHz\) \(1.3 MB\)](#)

 [Version 4.008 \(frequency 916 MHz\) \(1.3 MB\)](#)